

DESCRIPTION

ENEOS 4T is mineral based engine oil recommended for 4T engine motorcycles. ENEOS 4T optimises engine performance, fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation for daily use.

ADVANTAGES

- ✓ **Optimised Performance**
 - ENEOS 4T is made by blending selected mineral base oil and optimised additives. ENEOS 4T has good oxidation stability under high-temperature.
- ✓ **Excellent Clutch Performance**
 - ENEOS 4T is certified as JASO MA which resists clutch slipping, prevents clutch trouble and offers exceptional engine power and fuel economy.
- ✓ **Cleaning Performance Endurance**
 - ENEOS 4T minimises ash deposits in the engine and maintains engine cleanliness.

PERFORMANCE LEVEL

JASO MA

APPLICABLE VEHICLES

Recommended for all 4T engine motorcycles.

Suitable for Honda, Yamaha, Suzuki, Kawasaki and Korean and Chinese motorcycles.

CONTAINER SIZE

0.8 Litre

1 Litre

TYPICAL CHARACTERISTICS

SAE Grade		20W-40	20W-50	20W-50	SJ MA 40
API Performance Grade		SL		SJ	
JASO Grade		MA		MA	
Density (15°C) g/cm ³	ASTM D 4052	0.8727	0.8769	0.883	0.8850
Viscosity mm ² /s	(40°C)	118.8	149.5	160	127.5
	(100°C)	13.61	17.12	17.5	13.51
Viscosity Index	ASTM D 2270	111	124	120	101
Flash Point °C	ASTM D 92	258	260	252	256
Pour Point °C	ASTM D 97	-30	-27	-36	-18
Base Number	ASTM D 4684	7.6	7.6	7.58	6.04

Note: Typical characteristics are subject to change without notice (August, 2017)

Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations