

## DESCRIPTION

ENEOS 4T Synthetic is recommended for high-performance 4T motorcycles that delivers high power efficiency and acceleration. ENEOS 4T Synthetic exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions. ENEOS 4T Synthetic is excellent in maintaining high engine power and fuel economy with longer drain interval.

## ADVANTAGES

- ✓ **High-Temperature Oxidation Stability**
  - ENEOS 4T Synthetic is made of synthetic base oil and optimised additives. It has excellent oxidation stability under high-temperature.
- ✓ **Excellent Clutch Performance**
  - ENEOS 4T Synthetic is certified as JASO MA which resists clutch slipping. It prevents clutch trouble and offers excellent engine power and fuel economy.
- ✓ **Optimal Engine Cleanliness**
  - ENEOS 4T Synthetic minimises ashy deposits in the engine to keep the engine clean.

## INTERNATIONAL STANDARD

JASO MA

## APPLICABLE VEHICLES

Recommended for all scooters and motorcycles with 4T engines.

Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

\*Caution: For trouble prevention, please use proper viscosity grade oil for the motorcycles/scooters.

## CONTAINER SIZE

0.8 Litre

1 Litre

## TYPICAL CHARACTERISTICS

SAE Grade		10W-40	20W-40
API Performance Grade		SL	SJ
JASO Performance Grade		MA	MA
Density (15°C) g/cm <sup>3</sup>	ASTM D 4052	0.8639	0.8799
Viscosity mm <sup>2</sup> /s (40°C)	ASTM D 445	88.42	128.7
	ASTM D 445	13.38	14.42
Viscosity Index	ASTM D 2270	153	112
Flash Point °C	ASTM D 92	234	248
Pour Point °C	ASTM D 6749	-42	-39
Base Number	ASTM D 4684	-	6.85

Note: Typical characteristics are subject to change without notice (June, 2017)

### Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations

NOEA-NPS4198 (S4198)  
19 July 2017