

## DESCRIPTION

ENEOS SN/CF GF-5 5W-30 Fully-Synthetic is high-performance motor oil made with fully synthetic base oil and selected additives. This oil is blended with ENEOS Corporation's outstanding lubricant technologies. Designed for city driving and heavy load conditions, while providing excellent engine protection and improved fuel economy. Suitable for a wide range of modern vehicles and good emission control system compatibility.

## ADVANTAGES

- ✓ **Excellent Engine Protection**
  - Designed to operate under extreme conditions, while providing excellent engine protection at high temperature and high RPM. Active cleaning agents reduces sludge build-up and improves engine life and cleanliness.
- ✓ **Improved Fuel Economy**
  - Good frictional properties improved engine efficiency and improves fuel economy, lowering operating costs while providing the highest performance.
- ✓ **Enhanced Emission Control System Compatibility**
  - Reduce poisoning of gasoline catalytic converters.

## PERFORMANCE LEVEL

SN/CF      GF-5

## APPLICABLE VEHICLES

Recommend for all vehicles with high-performance gasoline engines, including turbocharged vehicles. (Daihatsu, Honda, Mitsubishi, Nissan, Toyota, BMW, Mercedes Benz, VW, Peugeot, Hyundai, Kia etc. vehicles.)

## CONTAINER SIZE

4 Litre      209 Litre

## TYPICAL CHARACTERISTICS

SAE Grade	5W-30	
API Performance Grade	SN/CF	
Density (15°C) g/cm <sup>3</sup>	ASTM D 4052	0.8507
Viscosity mm <sup>2</sup> /s (40°C)	ASTM D 445	54.42
	ASTM D 445	9.552
Viscosity Index	ASTM D 2270	161
Flash Point °C	ASTM D 92	238
Pour Point °C	ASTM D 6749	-42
Base Number	ASTM D 2896	5.83

Note: Typical characteristics are subject to change without notice (Nov 2020)

### Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations