

## DESCRIPTION

ENEOS Touring GT CF/SF 20W-50 is a high-performance engine oil made with highly refined base oil and selected additives. Suitable for gasoline and diesel engine in both passenger cars and commercial diesel vehicles, it is also suitable for vehicles using unleaded fuel or gas fuel (CNG & LPG).

## ADVANTAGES

- ✓ **Longer Oil and Engine Life**
  - ENEOS Touring GT CF/SF 20W-50 contains optimised additives which have significantly improved thermal stability, oxidative stability, soot dispersion, outstanding anti-wear and detergent-dispersant performance, resulting in longer oil and engine life.
- ✓ **Reduced Oil Consumption**
  - Due to excellent base oils, evaporation loss is very low even under high-temperature conditions. Consequently, only minimum amount of engine oil is required for top-up.
- ✓ **Keep Engine Clean**
  - Minimises ash deposits in the engine and keep the engine clean.

## INTERNATIONAL STANDARD

CF/SF

## APPLICABLE VEHICLES

Suitable for use in TATA, Ashok, Leyland, Eicher, Mahindra & Mahindra vehicles, trucks and buses.

Preferred choice of Japanese vehicles such as Toyota, Honda, Nissan, Mitsubishi, Suzuki, Daihatsu & Mazda.

## CONTAINER SIZE

1 Litre

5 Litre

18 Litre

## TYPICAL CHARACTERISTICS

Test Item	Test Method	20W-50
Density (15°C) g/cm <sup>3</sup>	ASTM D 4052	0.8854
Viscosity mm <sup>2</sup> /s (40°C)	ASTM D 445	176.1
	ASTM D 445	19.01
Viscosity Index	ASTM D 2270	122
Flash Point °C	ASTM D 92	248
Pour Point °C	ASTM D 97	-33
Base Number	ASTM D 4684	11.18
Colour	ASTM D 1500	RED
Odour	Smell	FRAGRANCE

Note: Typical characteristics are subject to change without notice (May, 2017)

**Safety Precaution:**

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations