

DESCRIPTION

ENEOS X SP GF-6A 0W-20 is a fully synthetic motor oil developed to deliver superior engine protection, enhanced fuel economy benefits, keep engine running like new and protect against engine components. This oil is blended with ENEOS Corporation's outstanding technologies.

ADVANTAGES

- ✓ **Outstanding Fuel Economy and Engineered for Performance**
 - Low-viscosity formulation that provides excellent fuel economy and environmental protection while delivering outstanding engine performance, protection, and cleanliness.
- ✓ **Prolong engine oil life and oil drain interval**
 - Specially formulated to maintain viscosity and controlling oxidation to minimise oil breakdown.
- ✓ **Overall Engine Protection**
 - Active cleaning agents (metal detergents and ash-less dispersants) prevent sludge deposits build-up for a longer and cleaner engine life.

PERFORMANCE LEVEL

SP
ILSAC GF-6A

APPLICABLE VEHICLES

0W-20 is recommended for hybrid cars and/or all types of cars where this viscosity is recommended. Recommended for cars made by world-leading manufacturers. Check user's manual for the manufacturer's recommended oil viscosity grade, API service classification.

Caution:

- The use of this oil in automobiles designed for high-viscosity oils can result in inadequate oil circulation, oil leaks and other problems. Only use for 0W-20 recommended automobiles such as hybrid cars.
- This oil should not be used for any diesel engine vehicles.

CONTAINER SIZE

4 Litre

TYPICAL CHARACTERISTICS

SAE Grade		0W-20
API Performance Grade		SP
Density (15°C) g/cm ³	ASTM D 4052	0.8460
Viscosity mm ² /s (40°C)	ASTM D 445	44.35
	ASTM D 445	8.35
Viscosity Index	ASTM D 2270	167
Flash Point °C	ASTM D 92	242
Pour Point °C	ASTM D 6749	-45
Base Number	ASTM D 2896	7.08

Note: Typical characteristics are subject to change without notice (Oct, 2022)

Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations