

DESCRIPTION

ENEOS X SP/CF SYNTHETIC BLENDED is a high-performance motor oil made with synthetic blended base oil and selected additives. Modern performance additives help provide longer engine life and superior protection for vehicles. This oil is blended with ENEOS Corporation's outstanding technologies..

ADVANTAGES

- ✓ Outstanding anti-wear protection under a wide variety of driving conditions.
- ✓ Protection against sludge, engine rust and corrosion under severe operating conditions
- ✓ Extends engine life and performance.

PERFORMANCE LEVEL

SP/CF

APPLICABLE VEHICLES

Recommended for gasoline and diesel engines in passenger cars and light duty commercial vehicles

Recommended for cars equipped with or without catalytic converters, turbo charged engines, soot filters and direct injection systems.

*Caution: For trouble prevention, please use proper viscosity grade oil for the car

CONTAINER SIZE

4 Litre

TYPICAL CHARACTERISTICS

| SAE Grade | | 5W-30 | 10W-40 |
|-------------------------------------|-------------|--------------|---------------|
| API Performance Grade | | SP/CF | SP/CF |
| ILSAC | | GF-6A | - |
| Density (15°C) g/cm ³ | ASTM D 4052 | 0.8575 | 0.8647 |
| Viscosity mm ² /s (40°C) | ASTM D 445 | 60.10 | 98.04 |
| | ASTM D 445 | 9.948 | 13.90 |
| Viscosity Index | ASTM D 2270 | 152 | 144 |
| Flash Point °C | ASTM D 92 | 246 | 248 |
| Pour Point °C | ASTM D 6749 | -42 | -36 |
| Base Number | ASTM D 2896 | 6.45 | 6.63 |

Note: Typical characteristics are subject to change without notice (Oct, 2022)

Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils.
- In case of physical contact, wash immediately with soap and water.
- Protect the environment by disposing off used oils as per local regulations.