

## DESCRIPTION

ENEOS MOTOR OIL SP/CF is a high-performance motor oil formulated from high quality base oils combined with performance additives to help provide long engine life and protect engine components from lubricant related failures. This oil is blended with ENEOS Corporation's outstanding technologies.

## ADVANTAGES

- ✓ **Exceptional Performance Engine Oil**
  - Blended with highly refined high-viscosity index mineral base oils and optimised additives, its high-temperature oxidation stability is superior compared to conventional engine oils made from other mineral base.
- ✓ **Extend Engine Life and Performance**
  - Protects engine with superior wear resistance under a wide variety of driving conditions.
- ✓ **Prevention of Sludge and Deposits Formation in the Engine**
  - Gives optimum protection sludge and deposits formation in the engine.

## PERFORMANCE LEVEL

SP/CF

## APPLICABLE VEHICLES

Recommended for all range of engines in cars and light commercial vehicles with gasoline and diesel engine.

Suitable for cars made by world-leading manufacturers.

## CONTAINER SIZE

1 Litre

4 Litre

209 Litre

## TYPICAL CHARACTERISTICS

SAE Grade		10W-30	15W-40	20W-50
API Performance Grade		SPCF	SP/CF	SP/CF
ILSAC		GF-6A	-	-
Density (15°C) g/cm <sup>3</sup>	ASTM D 4052	0.8673	0.8722	0.8808
Viscosity mm <sup>2</sup> /s	(40°C) ASTM D 445	63.17	101.6	163.70
	(100°C) ASTM D 445	9.865	13.29	17.85
Viscosity Index	ASTM D 2270	131	129	120
Flash Point °C	ASTM D 6749	238	258	256
Pour Point °C	ASTM D 97	-36.0	-33.0	-30.0
Base Number	ASTM D 2896	7.01	6.51	6.65

Note: Typical characteristics are subject to change without notice (Oct, 2022)

**Safety Precaution:**

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations