

FULLY SYNTHETIC

Higher Protection
Sludge and deposit protection
Low SAPS

Product Data Sheet

DESCRIPTION

ENEOS X Series brings the advanced technology and highest quality specifications standards together in the premium engine oils especially formulated for the latest generation of cars. The new range in ENEOS product line meets the highest emission norms and fuel saving standard, extend engine life through reduced sulphur content.

ADVANTAGES

ENEOS X SP/C2 0W-30 offers:

- Outstanding anti-wear protection under a wide variety of driving conditions.
- · Improves engine efficiency, lower fuel consumption and reduce emission to protect the environment.
- Excellent cold start, excellent wear protection, impressive engine cleanliness and greater oxidation stability.
- Maintaining viscosity and controlling oxidation to prevent oil breakdown.
- Extending engine life by working to prevent damaging deposits and sludge build up.

PERFORMANCE LEVEL

SP ACEA C2

APPLICABLE

- Gasoline and diesel engines cars where this viscosity is recommended.
- Designed to work with vehicles fitted with Three-Way Catalyst (TWC) & Diesel Particulate Filters (DPF).
- Recommended for cars made by world-leading manufactures.
- Check user's manual for the manufacturer's recommended oil viscosity grade, API and ACEA service classification.

CONTAINER SIZE

5 Litre 209 Litre

TYPICAL CHARACTERISTICS

SAE Grade			0W-30
API Performance Grade			SP
ACEA			C2
Density (15°C) g/cm³		ASTM D 4052	0.8419
Viscosity mm ² /s	(40°C)	ASTM D 445	54.00
	(100°C)	ASTM D 445	10.38
Viscosity Index		ASTM D 2270	185
Flash Point °C		ASTM D 6749	218
Pour Point °C		ASTM D 97	-42
Base Number		ASTM D 2896	7.29

Note: Typical characteristics are subject to change without notice (Dec, 2023)

Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations

EASIA Dec 2023