

## DESCRIPTION

ENEOS 4T Series is mineral based engine oil recommended for all 4T engine motorcycles and scooters. ENEOS 4T Series optimises engine performance, fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation for daily use. This oil is blended with ENEOS Corporation's outstanding lubricating technologies.

## ADVANTAGES

- ✓ **Optimised Performance**
  - ENEOS 4T series is made by blending selected mineral base oil and optimised additives. ENEOS 4T series has good oxidation stability under high temperature.
- ✓ **Excellent Clutch Performance**
  - ENEOS 4T is certified as JASO MA2 which resists clutch slipping, prevents clutch trouble and offers exceptional engine power and fuel economy.
- ✓ **Cleaning Performance Endurance**
  - ENEOS 4T series minimises ash deposits in the engine and maintains engine cleanliness.

## PERFORMANCE LEVEL

JASO MA2

## APPLICABLE VEHICLES

- All types of motorcycles and scooters with 4T engines where this viscosity is recommended.
- Recommended for all motorcycles and scooters made by world-leading manufacturers.
- Check user's manual for the manufacturer's recommended oil viscosity grade, API service classification.

## CONTAINER SIZE

1 Litre

## TYPICAL CHARACTERISTICS

SAE Grade		20W-40	20W-50
API Performance Grade		SL	
JASO Grade		MA2	
Density (15°C) g/cm <sup>3</sup>	ASTM D 4052	0.8786	0.8782
Viscosity mm <sup>2</sup> /s	(40°C)	121.8	154.0
	(100°C)	13.77	17.00
Viscosity Index	ASTM D 2270	110	119
Flash Point °C	ASTM D 92	252	252
Pour Point °C	ASTM D 97	-36	-33
Base Number	ASTM D 4684	5.46	5.85

Note: Typical characteristics are subject to change without notice (Apr, 2025)

### Safety Precaution:

- Avoid prolonged and repeated skin contact with used oils
- In case of physical contact, wash immediately with soap and water
- Protect the environment by disposing off used oils as per local regulations